REBAR STRAIGHTENER

Model: DBR-32WH

A dual-purpose tool that cleanly straightens bent rebars and functions as a simple bender. Accepts any 490N/mm^2 tensile strength rebar up to 32mm (1¼").

Max.rebar diameter	32mm (1¼")
Bending speed	4 sec / 90°
Max.tensile strength	490 N/mm^2
Bending angle	Up to 140°
Power supply	Single phase mains electricity / Generator
Voltage	100V/115V/230V
Power Input	1050W
Weight	26 kg
Dimensions (mm)	660x270x200

Rebar diameter	Straightening capacity		Bending capacity	
	Push	Pull	Push	Pull
13mm (1/2")	up to 125°	up to 121°	up to 94°	up to 92°
16mm (5/8")	128°	124°	90°	90°
20mm (3/4")	130°	126°	90°	90°
25mm (1")	132°	124°	90°	90°
29mm (1 1/8")	140°	135°	90°	90°
32mm (1 1/4")	144°	138°	90°	90°

REBAR STRAIGHTENER
รุ่น **DBR-32WH**

เป็นเครื่องมือ 2 ชนิดในเครื่องเดียว สามารถใช้ขืดเหล็กที่คดงอได้ และใช้เป็นเครื่องดัดเหล็กทั่วไปได้เช่นกัน รองรับความต้านทานแรงดึง 490N/มม^2 ขนาดเหล็กถึง 32 มม. (1¼")

ขนาด Ø เหล็กสูงสุด	32 มม. (1¼")
ความเร็วในการดัด	4 วินาที / 90°
ความต้านทานแรงดึงสูงสุด	490 N/มม^2
องศาในการดัด	มากถึง 140°
แหล่งจ่ายไฟ	Single phase mains electricity / เครื่องกำเนิดไฟฟ้า
แรงดันไฟฟ้า	100V/115V/230V
กำลังไฟฟ้า	1050 วัตต์
น้ำหนัก	26 กก.
ขนาด (มม)	660x270x200

ขนาด Ø เหล็ก	ความสามารถในการขืด		ความสามารถในการดัด	
	ดัน	ดึง	ดัน	ดึง
13mm (1/2")	มากถึง 125°	มากถึง 121°	มากถึง 94°	มากถึง 92°
16mm (5/8")	128°	124°	90°	90°
20mm (3/4")	130°	126°	90°	90°
25mm (1")	132°	124°	90°	90°
29mm (1 1/8")	140°	135°	90°	90°
32mm (1 1/4")	144°	138°	90°	90°